# GW-1200





## GW-1200

Economical semi-automatic turntable wrapping machines are reliable, safe and easy to use.



#### Efficiency

- Adjustable film-tension control
- Minimum consumption of film per pallet
- Optimization of cost per pallet

#### Safety

- Film carriage inside the tower
- Safe, fast and ergonomic film loading
- Safety switch for film loading door
- Emergency stop




#### **Simplicity**

- Fast and simple installation
- Safe transportation (machine packed in a wooden crate)
- Easy maintenance
- Height sensing by photocell (wrapping of dark colored goods also possible)
- Easy film feeding the film is just placed in the middle of the carriage and threaded through the threading slot



#### Easy to use

- Adjustable number of top and bottom wraps
- Adjustable carriage and turntable speed
- Reinforcing wrap function
- Soft START/STOP
- Load begins and ends in same position
- Adjustable overwrap



#### **Options**

- Access ramp
- Optional scale



#### **Oriented Machine Film Benefits**

- No waste due to knicked edges
- Guaranteed film consistency
- Ready to be applied with minor tension. No need to be pre-stretched.
- Consistent Film Delivery
- No Pre-Stretch carriage maintenece

### **Technical data**

Capacity

Power supply
Turntable speed
Turntable height
Film carriage

Machine dimensions: Turntable Ø: Space required:

Machine weight: Wrapping height: Max. pallet weight:

Pallet dimensions:

Up to 35 pallets/hr

(depending on pallet dimensions)

120V, single phase, 60Hz

2-12 rpm 3 1/4"

variable up/down speed

100" x 65"

65"

45.6 ft<sup>2</sup> (height 114") approx. 950 lbs.

90" 4.400 lbs.

65"L x 65"W x 90"H (max)

